Product Specification 6625-11

Taconic 6625-11 is a 11 mil aluminium foil flame spray tape with glass reinforcement and a high temperature silicone adhesive. This tape is designed for precision masking of components during flame spray and plasma spray coating applications and leaves little-to-no residue upon removal. The foil allows for precision coating lines and true edges. 6625-11 is self-wound with no release liner. Maximum width is 864 mm wide

Product Properties	Units	Value	Tolerance	Test Method
Adhesive Type		**Silicone**		
Substrate Type		**E-GLASS**		
Total Weight of Substrate	g/m2	**N/A**	+/-5%	ASTM D4969
% Coating of Substrate		**N/A**		
Substrate Thickness	micron	**157**		
Adhesive Thickness	micron	**109**		ASTM D3652
Total Product Thickness	micron	**266**		
Adhesive Strength	N/25,4mm	**13**	Typical	ASTM D3330 METHOD A
		9	Minimum	
Operating Temperature	°Celsius	**-73° to +260°**		

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.

QUALITY ISO 9001:2015 NSAI Certified
ENVIRONMENT ISO 14001:2015 NSAI Certified

Please contact us for samples or a quotation

Taconic International Ltd
Ireland
www.taconic-ipd.com
info@taconic-ipd.com

Taconic France
France
www.taconic-ipd.fr
info@taconic-ipd.fr

Taconic International Ltd
Germany
www.taconic.de
info@taconic.de

Wildcat Taconic
United Kingdom
www.taconic-ipd.com
info@wildcat-taconic.com

Taconic SP z.o.o
Poland
www.taconic-ipd.pl
biuro@4taconic.com

For queries in North America please visit www.4taconic.com or email info@4taconic.com

TÜV SÜD ISO 9001
REACH COMPLIANCE RoHS

Rev: 05/23 - 001