Product Specification A7060

Taconic's A7060 is a PTFE coated glass fibre product with the highest PTFE content and silicone adhesive, with a corrugated yellow backing liner. Mainly used as a high temperature release material in the packaging, plastics, PVC welding and composite industries as well as a liner in mould release and roller covering applications, A7060 is seen as offering best release, value and performance.. Standard width of A7060 is 1000mm with availability also as slit rolls from 10mm and upwards.

Product Properties	Units	Value	Tolerance	Test Method
Adhesive Type		**SILICONE**		
Substrate Type		**E-GLASS**		
Total Weight of Substrate	g/m2	**320**		ISO 2286-2
% Coating of Substrate	%	**67**		
Substrate Thickness	micron	**142**		
Adhesive Thickness	micron	**60**		ISO 2286-3
Total Product Thickness	micron	**202**		
Adhesive Strength	N/25,4mm	**12**	Typical	ISO 8510-2
		10	Minimum	
Operating Temperature	°Celsius	**-73° to +260°**		

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.

QUALITY ISO 9001:2015 NSAI Certified
ENVIRONMENT ISO 14001:2015 NSAI Certified

Please contact us for samples or a quotation

TÜV SÜD ISO 9001

Taconic International Ltd
Ireland
www.taconic-ipd.com
info@taconic-ipd.com

Taconic France
France
www.taconic-ipd.fr
info@taconic-ipd.fr

Taconic International Ltd
Germany
www.taconic.de
info@taconic.de

Wildcat Taconic
United Kingdom
www.taconic-ipd.com
info@wildcat-taconic.com

Taconic SP z.o.o
Poland
www.taconic-ipd.pl
biuro@4taconic.com

For queries in North America please visit www.4taconic.com or email info@4taconic.com

REACH COMPLIANCE RoHS

Rev: 05/21 - 002